



770 HI-TACK DOUBLE SIDED PVC

DESCRIPTION:

770 is a very strong transparent PVC film coated with a thick coating of a long aging high tack and high bond acrylic adhesive on both sides with white paper liner.

**PERFORMANCE
FEATURES:**

Because of the thick high tack adhesive, 770 bonds extremely well to both smooth and rough surfaces. The tape and adhesive are compatible with surfaces where normally plasticiser migration may be a problem. 770 is RoHS Compliant relative to Directive 2002/95/EC.

**TECHNICAL
SPECIFICATIONS:**

Adhesive Power	-	1220gm/cm
Thickness	-	0.25mm
Tensile Strength	-	3.27 Kg/cm
Elongation	-	60%
Temperature range	-	-40°C to +70°C

SIZES AVAILABLE:

6mm to 1000mm x 25M
6mm to 1000mm x 250M

APPLICATIONS:

Ideal for adhering acrylic sheeting and signs together. Great for making plastic extrusions self adhesive. Excellent for adhering nameplates and labels to metal and powder coated metal surfaces.

**SURFACE
PREPARATION:**

This product should always be applied to clean, dry grease and dust free surface. Care should be taken to obtain maximum benefit from the pressure sensitive adhesive. Optimum performance will be obtained when the bond is formed at 23°C. At low temperatures there is a chance of condensation and the tack of the adhesive can be reduced. For maximum performance on some low surface energy substrates an adhesion promoter may be required. We recommend the use of Stylus AP-1 Adhesion Promoter (primer) where indicated on the Stylus Surface Energy List

The above information is given in good faith for guidance only and not specification purposes. All data is based upon average values, the Purchaser shall be responsible for determining the suitability of this product for their purposes.

August 2007