



**VIBAC PP30 POLYPROPYLENE
PACKAGING TAPE.**

DESCRIPTION:

PP30 is made from a premium grade 28µm O.P.P. film coated with an aggressive solvent natural rubber based adhesive.
Colours: Brown, Transparent, White

**PERFORMANCE
FEATURES:**

The excellent combination of aggressive adhesive, strong backing film and consistent unwind make Vibac PP30 ideal for sealing all sizes of cartons and grades of board used for packaging of products manufactured throughout Australia and the world.

**TECHNICAL
SPECIFICATIONS:**

Tensile Strength: - 4.5Kg/cm
Thickness - Backing Film: - 28µm(0.028mm)±10%
- **Adhesive:** - 17.5µm(0.0175mm)±10%
- **Total:** - 45.5µm(0.0455mm)±10%
Adhesive Power: - 250 gm/cm
Elongation: - 140%
Application Temperature: - 10° to 35°C
Service Temperature: - - 20° to 76°C

SIZES AVAILABLE:

25mm x 75M BR/TR,
36mm x 75M BR/TR,
48mm x 75M BR/TR/WH,
75mm x 75M TRANS

APPLICATIONS:

General purpose, high volume packaging and bundling applications by hand dispensers.

The above information is given in good faith for guidance only and not specification purposes. All data is based upon average values, the Purchaser shall be responsible for determining the suitability of this product for their purposes.

April 2007